

STYLEX

Disassembly and Recycling Document

Model: Cove Table

Disassembly Time: 10min / No Special Training Required

Refer to Stylex website for model variations


Tools Required

- Safety glasses
- 3/8" Hex Key
- 5/32" Hex Key
- Flathead Screwdriver



Breakdown Steps

1. Turn table upside down. Using the 5/32" hex key, remove the 6 mounting screws connecting the top mounting plate to the table top. Lift and remove base from the top. (Figure A1).



2. Flip the base upright. Using a 3/8" hex key, remove the bolt attaching the top mounting plate to the column. Separate the top mounting plate and adapter plate from the column assembly after removing the set screws (Figure B1).



3. Flip the base upside down. Using a 3/8" hex key, remove the bolt attaching the 4-leg base to the column assembly. Separate the column from the 4-leg base (Figure C1).



4. Remove the glides from the base using a flat head screw driver if necessary.

Exploded Product Assembly

- Table Top
- Material: MDF, Laminate, Wood, Acrylic
- Screw **↑**
- Material: Steel
- Set Screws **↑↑**
- Material: Steel
- Adapter Plate
- Material: Steel

- Top Mounting Plate
- Material: Aluminum

- Screws **↑↑↑↑↑↑**
- Material: Steel

- Table Column
- Material: Steel

- 4 Blade Base
- Material: Aluminum

- Screw **↑**
- Material: Steel

