

# stylex




Lena

# Lena

(Click [here](#) to view full 72-color palette and order memo samples)



6644  
Azure



8050  
Snow



8000  
White



3392  
Ming



3328  
Camel



5478  
Caramel



8023  
Clay



2511  
Ferrari



6622  
Cardinal



5484  
Salsa



3368  
Chateau



2257  
Java



3370  
Espresso



3364  
Sequoia



3324  
Nutmeg



3326  
Alba



1414  
Café Latte



3390  
Safari



3396  
Linen



3394  
Pietra



3388  
Putty



1464  
Elfin




9200  
Quahog



2526  
Sterling




1413  
Greystone



2523  
Mystic



9187  
Onda



2208  
Ghiaccio



3348  
Tahoe



9199  
Heather




2500  
Pewter



443  
Mariner



2583  
Cobalt



9000  
Black



5454  
Celtic



2561  
Evergreen



9188  
Acqua

# Lena

---

Full grain leather with even coloration throughout the entire hide. Superior selection of European and New Zealand cattle hides are hand selected for Lena. These hides are recognized industry wide for their clean surfaces and excellent cutting yields. Luxurious soft hand and smooth supple surface make this one of the most beautiful leathers available. The protective finish allows Lena to be suitable for most public and private environments.

REACH (EC 1907/2006) compliant production aims to improve the protection of human and environmental health. Processed using low emission mineral tanning formulas which are environmentally respectful, the hides are retanned in aged oak drums using vegetable agents, natural fat liquors, oils and dyes that ensure the leather is properly through dyed. Natural color variations may occur even within the same dye lot.

---

**Application:** Aviation\*, Contract, Hospitality, Residential, Marine\*\*

**Raw Material:** European and New Zealand

**Hide Size:** Average 48 sqft

**Thickness:** 0.9 to 1.0 mm

**Wet Rub Test:** (Nr 150): IUF 450 / UNI EN ISO 11640:  $\geq 4$  grey scale

**Dry Rub Test:** (Nr 500): IUF 450 / UNI EN ISO 11640:  $\geq 4$  grey scale

**Abrasion:** (ASTM D 3884-92) 500 gram load: 1500 cycles

**Abrasion:** Wyzenbeek (ASTM D4157) 100,000 Rubs

**Alkaline ph 8:** IUF 450 / UNI EN ISO 11640:  $\geq 4$  grey scale

**Flexing Endurance:** IUP 20:  $\geq 30,000$

**Tear Strength:** IUP 40 / UNI EN ISO 3377-I:  $\geq 20$  N

**Adhesion:** IUF 470 / UNI EN ISO 11644:  $\geq 3.50$  N/cm

**Water repellency:** AATCC 22-2010: 93

**Light resistance (Xenon Test):** IUF 402 / UNI EN ISO 105-B02: 5 blue scale

**Flammability Resistance:** UFAC Class 1, CAL TB 117-2013, NFPA 260

**Soil/Stain Release:** AATCC 130-2015: Grade 5 represents best stain removal (immediate). Nail polish remover (5), Betadine (5), Bleach (5), Urine (5), Blood (5). Fluid Resistance: Red wine (5), Beer (5), Whiskey (4.5), Cola (5), Coffee (4.5), Red Bull (5) Mayonnaise (5), Olive Oil (5), Catsup (5), Vegetable oil (5), Chocolate (melted) (5), Lipstick (3.5), Lysol (5), Formula 409 (5), Windex (5). Test procedure modified to clean stains with 1 part household bleach/10 parts water solution.

**Bleach Cleanable:** BIFMA Health Care Furniture 8.1-2017 Section 7: Household bleach (sodium hypochlorite). CDC/EPA recommended ratios (1:48) parts bleach to water for the sanitizing and disinfecting of viruses and bacteria. Reference CDC/EPA and product specifications for approved dilution ratio and cleaning agent instructions for dwell time.

**Origin:** Italy

---

\*May be treated to meet Federal Aviation Regulations for Flammability Resistance.

\*\*May be treated to meet Wheelmark IMO Resolution A.652(1b).